CISC 3115 TY3 CO9a: Inheritance

Hui Chen

Department of Computer & Information Science
CUNY Brooklyn College

Outline

- Inheritance
 - Superclass/supertype, subclass/subtype
- Inheritance and constructors in Java
- Inheritance and instance methods in Java
- The Object class in Java

Class and Type

- A class defines a type, and often models a set of entities
- Example: to build a system for managing business at Brooklyn College, we consider
 - People, a set of individuals (objects), modeled as a class that captures the essence of the set of objects

People at Brooklyn College


Subtypes

- Some people at Brooklyn are different from the others in some way
- Professors and students are subtypes of Brooklyn College People



Type Hierarchy

- Characteristics and behavior
 - What are Students and Professors in common?
 - What are Students and Professors different?



What's in Common?


- What characteristics (attributes) and behavior (actions) do People at Brooklyn College have in common?
 - Characteristics (attributes, fields, or states):
 name, ID, address, email, phone, ...
 - Behavior (actions, functions, or methods): change address, apply parking, ...

What's Special?

- What's distinct about students?
 - Characteristics (attributes, fields, or states): classes taken, tuition and fees, ...
 - Behavior (actions, functions, or methods): add class, drop class, pay tuition, ...
- What's distinct about professors?
 - Characteristics (attributes, fields, or states): course taught, rank, title, ...
 - Behavior (actions, functions, or methods): register grade, apply promotion, ...

Inheritance & Type Hierarchy

 A subtype (child) inherits characteristics (data fields & methods) and behavior (actions) of its super/base type (parent)




Terms of Choice

- Terms
 - Super type, Super class
 - Base type, Base class
 - Parent type, parent class
 - Child type, child class
 - Subtype, subclass
 - ...
- In Java, we sometimes consider "type" and "class" are slightly different
 - In Java, a pure abstract class is called an "interface" (to be discussed in the future)

Example: Realizing the Type Hierarchy

· Classes: Person, Student, Professor



Super Type (Super Class): Person

```
public class Person {
          private String name;
          private String id;
          private String address;
          public Person(String name, String id, String address) {
                    this.name = name; this.id = id; ...
          public void changeAddress(String address) { ... }
... }
```

Subtype (Subclass): Student

```
public class Student extends Person {
         public final static int MAX_NUM_COURSES = 10;
         private String[] classesTaken;
         public Student(String name, String id, String address) {
                   ...... // initializing inherited data fields
                   classesTaken = new String[MAX_NUM_COURSES];
         public void haveTakenClass(String className) { ... }
         public void showClassesTaken() { ... }
```

Subtype (Subclass): Professor


```
public class Professor extends Person {
         public final static int SABATTICAL_LEAVE_INTERVAL = 7;
         private int yearStarted;
         public Professor(String name, String id, String address, int yearStarted) {
                   ...... // initializing inherited data fields
                   <u>this</u>.yearStarted = yearStarted;
         public void applySabbatical(int applicationYear) { ...
```

Questions

- Concepts
 - Type, subtype, class, subclass
 - Inheritance

UML Diagram and Type Hierarchy

- UML diagram for showing class hierarchy
- Example:
 GeometricObject,
 Circle, Rectangle




Constructors

- · Let us consider
 - Circle c = new Circle();
- Are superclass's constructor inherited?
 - No. They are not inherited.
 - They are invoked explicitly or implicitly.
 - Explicitly using the super keyword.

Constructors

- Let us considerCircle c = new Circle();
- Are superclass's Constructor Inherited?
- In other words, how are the data fields initialized?



Constructors in Super- and Sub-Classes

- Are superclass's Constructor Inherited?
 - No. They are not inherited, but one is always invoked
 - They are invoked <u>explicitly</u> or <u>implicitly</u>.
 - Explicitly using the super keyword
 - Implicitly the superclass's no-arg constructor is automatically invoked if the keyword <u>super</u> is not explicitly used.

Implicit Invocation of Superclass's Constructor


- A superclass's constructor is always invoked even if it isn't invoked explicitly using super.
- Which constructor is invoked implicitly?

Explicit Invocation of Superclass's Methods

- super refers to the superclass
- Use it
 - To call a superclass constructor
 - Java requires that the statement that uses the keyword <u>super</u> appear first in the constructor.
 - To call a superclass method

Constructor Chaining

- Invocation of superclass's constructor (along the inheritance chain)
- Example
 - · Consider classes: Person, Employee, Faculty



Constructor Chaining: Example

```
class Person {
 public Person() {
  System.out.println("(1) Person's no-arg constructor is
invoked");
class Employee extends Person {
 public Employee() {
  this("(2) Invoke Employee's overloaded constructor");
  System.out.println("(3) Employee's no-arg constructor is
invoked");
```

```
class Employee(String s) {
  System.out.println(s);
class Faculty extends Employee {
 public static void main(String[] args) {
  new Faculty();
 public Faculty() {
  System.out.println("(4) Faculty's no-arg constructor
is invoked");
```

Discussion: No-Arg Constructor

 Is there an error in the code below, and why? public class Apple extends Fruit { public class Fruit { public Fruit(String name) { System.out.println("Fruit's constructor is invoked");

Questions?

- Constructors in superclass
 - Explicit and implicit invocation
- Constructor chaining

Defining a Subclass

- A subclass inherits from a superclass.
- · One can also:
 - Add new properties
 - Add new methods
 - Override the methods of the superclass

Overriding Methods in Superclass

Modify the implementation of a method defined in the superclass

```
public class Circle extends GeometricObject {
    // Other methods are omitted

    /** Override the toString method defined in
    GeometricObject */
    public String toString() {
        return super.toString() + "\nradius is " + radius;
    }
}
```

Invoking Superclass's Instance Method

- Example
 - One could rewrite the printCircle() method in the Circle class as follows:

```
public void printCircle() {
    System.out.println("The circle is created " +
        super.getDateCreated() + " and the radius is " +
    radius);
}
```

Discussion: Method Overriding

 Can you override a private method in the superclass?

Discussion: Method Overriding

- Can you override a private method in the superclass?
 - No
- An instance method can be overridden only if it is accessible.
- A private method is not accessible outside its own class.
- A private method in the superclass can only be accessible in the superclass itself, is inaccessible in the subclass.
- Thus a private method cannot be overridden.

Discussion: Unrelated Methods

 Can you have a method whose <u>signature</u> is identical to a private method in the superclass?

Discussion: Unrelated Methods

- Can you have a method whose <u>signature</u> is identical to a <u>private</u> method in the superclass?
 - Yes
- However, this isn't method overriding. The two methods are unrelated, but happen to have the identical name.

Discussion: Static Method

- Like an instance method, a static method can be inherited.
- However, a static method cannot be overridden.
- If a static method defined in the superclass is redefined in a subclass, the method defined in the superclass is hidden.

Overriding vs. Overloading

 Overriding is to redefine the method with the identical signature in the superclass

```
public class Test {
  public static void main(String[] args) {
    A = new A();
    a.p(10);
    a.p(10.0);
class B {
 public void p(double i) {
    System.out.println(i * 2);
class A extends B {
  // This method overrides the method in B
  public void p(double i) {
    System.out.println(i);
```

```
public class Test {
   public static void main(String[] args) {
        A a = new A();
        a.p(10);
        a.p(10.0);
   }
}

class B {
   public void p(double i) {
        System.out.println(i * 2);
   }
}

class A extends B {
   // This method overloads the method in B
   public void p(int i) {
        System.out.println(i);
   }
}
```

Two methods with identical name but different signature

Questions?

- Defining subclasses
- A few topics
 - Invoking superclass's methods (constructors and instance methods)
 - Overriding
 - · Overriding and overloading

Codelab Exercise

 Codelab exercises marked as due by 10/04/2018

▶ 世 Constructors	14	2018/10/04
▶ ⊕ ☑ Static Member Variables	0	yyyy/mm/dd
▶ ⊕ Static Methods	5	2018/10/04
▶ ⊕ equals method	1	yyyy/mm/dd
▶ ⊕ methods	0	yyyy/mm/dd
▶ ⊕ ✓ toString method	2	2018/10/04

In-Class Exercise C09a-1

- Listings 11.1 11.3 in the textbook define 3 classes:
 GeometricObject, Circle, and Rectangle. In this exercise you are to add two classes to the hierarchy, Triangle and EquilateralTriangle, and write a client class to use the Triangle and EquilateralTriangle classes.
 - Create a CO9a-1 directory in the directory that hosts your weekly programming repository, work at the directory
 - The Triangle class is a subclass to GeometricObject, and the EquilateralTriangle is a subclass to Triangle. An EquilateralTriangle is a triangles whose sides are equal.
 - Your submission should include 6 files (6 classes): GeometricObject.java, Circle.java, Rectangle.java, Triangle.java, EquilateralTriangle, and TriangleClient.java
 - Use git to make a submission