

Inter-Process Communication (IPC)

Hui Chen ^a

^aCUNY Brooklyn College

October 16, 2024

Outline

- 1 Motivation
- 2 IPC
 - Shared Memory
 - Message Passing
- 3 Producer and Consumer Problem
- 4 UNIX (POSIX) and Windows IPC
- 5 Sharing Data among Threads and Processes

Outline

- 1 Motivation
- 2 IPC
 - Shared Memory
 - Message Passing
- 3 Producer and Consumer Problem
- 4 UNIX (POSIX) and Windows IPC
- 5 Sharing Data among Threads and Processes

Independent or Cooperating Processes

Processes within a system may be independent or cooperating.

- ▶ *Independent process* cannot affect or be affected by the execution of another process
- ▶ *Cooperating process* can affect or be affected by the execution of another process
 - ▶ Information sharing
 - ▶ Computation speed-up
 - ▶ Modularity

Multiprocess Architecture

Taking advantage of *independent* or/and cooperative processes, design multiprocess architecture applications

Example Applications

- ▶ The Chromium projects
- ▶ The instructor's Monte Carlo simulation program to estimate π
- ▶ Shell scripts

What benefits do we get by using the multiprocess architecture?

Outline

- 1 Motivation
- 2 IPC
 - Shared Memory
 - Message Passing
- 3 Producer and Consumer Problem
- 4 UNIX (POSIX) and Windows IPC
- 5 Sharing Data among Threads and Processes

Inter-process Communication (IPC)

- ▶ Cooperative processes communicate with each other to share data.
- ▶ There are two communication *models*
 - ▶ Shared memory
 - ▶ Message passing

Shared Memory

- ▶ OS must provide a system call to create a shared memory region.
- ▶ OS must attach the shared memory region to communicating processes' address spaces.
- ▶ OS must remove the restriction that normally one process is prevented from accessing another process's memory.
- ▶ All accesses to the shared memory region are treated as routine memory accesses, and no assistance from the kernel is required.
- ▶ The processes are also responsible for ensuring that they are not writing to the same location simultaneously.

Message Passing

- ▶ Processes exchange messages. There is no conflict needed to be avoided.
- ▶ IPC facility provides two operations:
 - ▶ `send(message)`
 - ▶ `receive(message)`
- ▶ Processes establish a communication link between them and exchange messages via `send/receive`

Design Message Passing

- ▶ Physical communication link can be shared memory, hardware bus, or network.
- ▶ Logically, the communication be
 - ▶ direction or indirect communication (like mailbox)
 - ▶ Blocking or non-blocking (synchronous or asynchronous)
 - ▶ explicit buffering or implicit (automatic) buffering

Outline

- 1 Motivation
- 2 IPC
 - Shared Memory
 - Message Passing
- 3 **Producer and Consumer Problem**
- 4 UNIX (POSIX) and Windows IPC
- 5 Sharing Data among Threads and Processes

Producer and Consumer Problem

The producer produces information while the consumer consumes information

Bounded Buffer via Shared Memory

Shared Buffer

```

1 #define BUFFER_SIZE 10
2 typedef struct { } item;
3
4 // The following are shared among cooperating processes
5 item buffer[BUFFER_SIZE];
6 int in = 0;
7 int out = 0;
8

```

Producer

```

1 while (true) { /* produce an item in next
   produced */
2   while (counter == BUFFER_SIZE)
3     ; /* do nothing */
4   buffer[in] = next_produced;
5   in = (in + 1) % BUFFER_SIZE;
6   counter++;
7 }
8

```

Consumer

```

1 while (true) {
2   while (counter == 0)
3     ; /* do nothing */
4   next_consumed = buffer[out];
5   out = (out + 1) % BUFFER_SIZE;
6   counter--;
7   /* consume the item in next consumed
   */
8 }
9

```

Process Synchronization

Both producer and consumer may read and write to the shared memory concurrently ...

Producer and Consumer via Blocking Message Passing

Producer

```
1 message next_produced;  
2 while (true) {  
3     /* produce an item in next_produced */  
4     send(next_produced); /* blocking */  
5 }  
6  
7
```

Consumer

```
1 message next_consumed;  
2 while (true) {  
3     receive(next_consumed); /* blocking */  
4     /* consume the item in next_consumed  
5         */  
6 }
```


How about non-blocking message passing?

Outline

- 1 Motivation
- 2 IPC
 - Shared Memory
 - Message Passing
- 3 Producer and Consumer Problem
- 4 UNIX (POSIX) and Windows IPC
- 5 Sharing Data among Threads and Processes

UNIX IPC

Examine the example programs

- ▶ POSIX ordinary and named pipes
- ▶ POSIX shared memory
- ▶ POSIX message passing
- ▶ Berkeley Sockets

Windows IPC

Examine the example programs

- ▶ Windows anonymous and named pipes
- ▶ Windows mail slots
- ▶ Windows shared memory

Outline

- 1 Motivation
- 2 IPC
 - Shared Memory
 - Message Passing
- 3 Producer and Consumer Problem
- 4 UNIX (POSIX) and Windows IPC
- 5 Sharing Data among Threads and Processes

Which data sharing or IPC mechanism to use?

- ▶ Processes, or threads, or both?
- ▶ How do processes share data?
- ▶ How do threads share data?