

L14: Identify and Anonymity



Hui Chen, Ph.D.

Dept. of Engineering & Computer Science

Virginia State University

Petersburg, VA 23806

Acknowledgement

- Many slides are from or are revised from the slides of the author of the textbook
 - Matt Bishop, Introduction to Computer Security, Addison-Wesley Professional, October, 2004, ISBN-13: 978-0-321-24774-5. [Introduction to Computer Security @ VSU's Safari Book Online subscription](#)
 - <http://nob.cs.ucdavis.edu/book/book-intro/slides/>

Outline

- Identity on the Web: hosts and domains; state and cookies
- Anonymity on the Web

Identity on the Web

- Host identity
 - Static identifiers: do not change over time
 - Dynamic identifiers: changes as a result of an event or the passing of time
- State and Cookies
- Anonymity
 - Anonymous email
 - Anonymity: good or bad?

Host Identity

- ❑ Host not connected to any networks
 - Pick any names; names are local
- ❑ Host connected to networking
 - Bound up to networking
 - One or more names depending on interfaces, network structure, and context
- ❑ Name and address
 - *Name* identifies principal
 - *Address* identifies location of principal
 - ❑ May be virtual location (network segment) as opposed to physical location (room 222)

Example

- ISO/OSI 7 model
 - A context for the issue of naming
- 7-layer model
 - Principals exist at each layer
 - MAC layer
 - Ethernet address: 00:05:02:6B:A8:21
 - AppleTalk address: network 51, node 235
 - Network layer
 - IP address: 192.168.35.89
 - Transport layer
 - Host name: example.com

Danger of Spoofing

- Attacker spoofs identity of another host
 - Protocols at, above the identity being spoofed will fail
 - They rely on spoofed, and hence faulty, information
- Example: spoof IP address, mapping between host names and IP addresses

Domain Name Server

- ❑ Maps transport identifiers (host names) to network identifiers (host addresses)
 - Forward records: host names → IP addresses
 - Reverse records: IP addresses → host names
- ❑ Weak authentication
 - Not cryptographically based
 - Various techniques used, such as reverse domain name lookup

Reverse Domain Name Lookup

- Validate identity of peer (host) name
 - Get IP address of peer
 - Get associated host name via DNS
 - Get IP addresses associated with host name from DNS
 - If first IP address in this set, accept name as correct; otherwise, reject as spoofed
- If DNS corrupted, this will not work

Domain Names: Example

```
$ dig www.google.com
```

```
; <<>> DiG 9.9.5-3ubuntu0.5-Ubuntu <<>> www.google.com
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 54988
;; flags: qr rd ra; QUERY: 1, ANSWER: 5, AUTHORITY: 0,
ADDITIONAL: 1
```

```
;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags::; MBZ: 0005 , udp: 4000
;; QUESTION SECTION:
;www.google.com.          IN      A
```

```
;; ANSWER SECTION:
www.google.com.         5      IN      A       74.125.228.244
www.google.com.         5      IN      A       74.125.228.240
www.google.com.         5      IN      A       74.125.228.243
www.google.com.         5      IN      A       74.125.228.241
www.google.com.         5      IN      A       74.125.228.242
```

```
;; Query time: 5 msec
;; SERVER: 192.168.101.2#53(192.168.101.2)
;; WHEN: Mon Nov 16 09:22:12 EST 2015
;; MSG SIZE rcvd: 123
```

10/26/2015

```
$ dig -x 74.125.228.244
```

```
; <<>> DiG 9.9.5-3ubuntu0.5-Ubuntu <<>> -x 74.125.228.244
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 34185
;; flags: qr rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0,
ADDITIONAL: 1
```

```
;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags::; MBZ: 0005 , udp: 4000
;; QUESTION SECTION:
;244.228.125.74.in-addr.arpa. IN      PTR
```

```
;; ANSWER SECTION:
244.228.125.74.in-addr.arpa. 5      IN      PTR     iad23s24-in-f20.1e100.net.
;; Query time: 49 msec
;; SERVER: 192.168.101.2#53(192.168.101.2)
;; WHEN: Mon Nov 16 09:23:16 EST 2015
;; MSG SIZE rcvd: 95
```

CSCI 451 - Fall 2015

10

Dynamic Identifiers

- ❑ Assigned to principals for a limited time
 - Server maintains pool of identifiers
 - Client contacts server using *local identifier*
 - ❑ Only client, server need to know this identifier
 - Server sends client *global identifier*
 - ❑ Client uses global identifier in other contexts, for example to talk to other hosts
 - ❑ Server notifies intermediate hosts of new client, global identifier association

Example: DHCP

- ❑ DHCP server has pool of IP addresses
- ❑ Laptop sends DHCP server its MAC address, requests IP address
 - MAC address is local identifier
 - IP address is global identifier
- ❑ DHCP server sends unused IP address
 - Also notifies infrastructure systems of the association between laptop and IP address
- ❑ Laptop accepts IP address, uses that to communicate with hosts other than server

Example: Gateways

- ❑ Laptop wants to access host on another network
 - Laptop's address is 10.1.3.241
- ❑ Gateway assigns legitimate address to internal address
 - Say IP address is 101.43.21.241
 - Gateway rewrites all outgoing, incoming packets appropriately
 - Invisible to both laptop, remote peer
- ❑ Internet protocol NAT works this way

Weak Authentication

- ❑ Static: host/name binding fixed over time
- ❑ Dynamic: host/name binding varies over time
 - Must update reverse records in DNS
 - ❑ Otherwise, the reverse lookup technique fails
 - Cannot rely on binding remaining fixed unless you know the period of time over which the binding persists

DNS Security Issues

- Trust is that name/IP address binding is correct
- Goal of attacker: associate incorrectly an IP address with a host name
 - Assume attacker controls name server, or can intercept queries and send responses

Attacks

- ❑ Change records on server
- ❑ Add extra record to response, giving incorrect name/IP address association
 - Called “cache poisoning”
- ❑ Attacker sends victim request that must be resolved by asking attacker
 - Attacker responds with answer plus two records for address spoofing (1 forward, 1 reverse)
 - Called “ask me”

Cookies

- ❑ Token containing information about state of transaction on network
 - Usual use: refers to state of interaction between web browser, client
 - Idea is to minimize storage requirements of servers, and put information on clients
- ❑ Client sends cookies to server

Some Fields in Cookies

- *name, value*: name has given value
- *expires*: how long cookie valid
 - Expired cookies discarded, not sent to server
 - If omitted, cookie deleted at end of session
- *domain*: domain for which cookie intended
 - Consists of last n fields of domain name of server
 - *Must* have at least one “.” in it
- *secure*: send only over secured (SSL, HTTPS) connection

Cookie: Example

- Caroline puts 2 books in shopping cart at books.com
 - Cookie: *name* bought, *value* BK=234&BK=8753, *domain* .books.com
- Caroline looks at other books, but decides to buy only those
 - She goes to the purchase page to order them
- Server requests cookie, gets above
 - From cookie, determines books in shopping cart

Who Can Get the Cookies?

- ❑ Web browser can send *any* cookie to a web server
 - Even if the cookie's domain does not match that of the web server
 - Usually controlled by browser settings
- ❑ Web server can *only* request cookies for its domain
 - Cookies need not have been sent by that browser

Where Did the Visitor Go?

- ❑ Server books.com sends Caroline 2 cookies
 - First described earlier
 - Second has *name* “id”, *value* “books.com”, *domain* “adv.com”
- ❑ Advertisements at books.com include some from site adv.com
 - When drawing page, Caroline’s browser requests content for ads from server “adv.com”
 - Server requests cookies from Caroline’s browser
 - By looking at *value*, server can tell Caroline visited “books.com”

Anonymity on the Web

- Recipients can determine origin of incoming packet
 - Sometimes not desirable
- Anonymizer: a site that hides origins of connections
 - Usually a proxy server
 - User connects to anonymizer, tells it destination
 - Anonymizer makes connection, sends traffic in both directions
 - Destination host sees only anonymizer

Example: *anon.penet.fi*

- ❑ Offered anonymous email service
 - Operated by Johan Helsingius in Finland 1993 – 1996
 - ❑ See https://w2.eff.org/Privacy/Anonymity/960830_penet_closure.announce and <http://waste.informatik.hu-berlin.de/Grassmuck/Texts/remailer.html>
 - Sender sends letter to it, naming another destination
 - Anonymizer strips headers, forwards message
 - ❑ Assigns an ID (say, 1234) to sender, records real sender and ID in database
 - ❑ Letter delivered as if from anon1234@anon.penet.fi
 - Recipient replies to that address
 - ❑ Anonymizer strips headers, forwards message as indicated by database entry

Problem

- ❑ Anonymizer knows who sender and recipient *really* are
- ❑ Called *pseudo-anonymous remailer* or *pseudonymous remailer*
 - Keeps mappings of anonymous identities and associated identities
- ❑ If you can get the mappings, you can figure out who sent what

More *anon.penet.fi*

- ❑ Material claimed to be copyrighted sent through site
- ❑ Finnish court directed owner to reveal mapping so plaintiffs could determine sender
- ❑ Owner appealed, subsequently shut down site

Cypherpunk Remailer

- ❑ See <http://www.cypherpunks.to/remailers/>
- ❑ Remailer that deletes header of incoming message, forwards body to destination
- ❑ Also called *Type I Remailer*
- ❑ No record kept of association between sender address, remailer's user name
 - Prevents tracing, as happened with *anon.penet.fi*
- ❑ Usually used in a chain, to obfuscate trail
 - For privacy, body of message may be enciphered

Cypherpunk Remailer Message

- ❑ Encipher message
- ❑ Add destination header
- ❑ Add header for remailer n
- ...
- ❑ Add header for remailer 2

send to remailer 1

send to remailer 2

send to Alice

*Hi, Alice,
It's SQUEAMISH
OSSIFRIGE
Bob*

Weaknesses

- ❑ Attacker monitoring entire network
 - Observes in & out flows of remailers
 - Goal is to associate incoming & outgoing messages
- ❑ If messages are clear text, trivial
 - So assume all messages enciphered
- ❑ So use traffic analysis!
 - Used to determine information based simply on movement of messages (traffic) around the network

Attacks

- If remailer forwards message before next message arrives, attacker can match them up
 - Hold messages for some period of time, greater than the message interarrival time
 - Randomize order of sending messages, waiting until at least n messages are ready to be forwarded
 - Note: attacker can force this by sending $n-1$ messages into queue


Attacks

- ❑ As messages forwarded, headers stripped so message size decreases
 - Pad message with garbage at each step, instructing next remailer to discard it
- ❑ Replay message, watch for spikes in outgoing traffic
 - Remailer can't forward same message more than once

Mixmaster Remailer

- ❑ See <http://mixmaster.sourceforge.net/>
- ❑ Cypherpunk remailer that handles only enciphered mail and pads (or fragments) messages to fixed size before sending them
- ❑ Designed to hinder attacks on Cypherpunk remailers
 - Messages uniquely numbered
 - Fragments reassembled *only* at last remailer for sending to recipient
- ❑ Also called Type II Remailer

Cypherpunk Remailer Message



HTTP over TLS

- ❑ Encrypt the traffic
- ❑ Hide the portion of the website you are visiting
- ❑ HTTP Everywhere project
 - The Electronics Frontier Foundation
 - <https://www.eff.org/https-everywhere>

Tor

- Hide identity in a *crowd*
- Connecting through a series of virtual tunnels via Onion routers
- <https://www.torproject.org>

Anonymity

- Some purposes for anonymity
 - Removes personalities from debate
 - With appropriate choice of pseudonym, shapes course of debate by implication
 - Prevents retaliation
- Are these benefits or drawbacks?
 - Depends on society, and who is involved

Privacy

- ❑ Anonymity protects privacy by obstructing amalgamation of individual records
- ❑ Important, because amalgamation poses 3 risks:
 - Incorrect conclusions from misinterpreted data
 - Harm from erroneous information
 - Not being let alone
- ❑ Also hinders monitoring to deter or prevent crime
- ❑ Conclusion: anonymity can be used for good or ill
 - Right to remain anonymous entails responsibility to use that right wisely

Summary

- ❑ Identity specifies a principal (unique entity)
 - Same principal may have many different identities
 - ❑ Function (role)
 - ❑ Associated principals (group)
 - ❑ Individual (user/host)
 - These may vary with view of principal
 - ❑ Different names at each network layer, for example
 - Anonymity possible; may or may not be desirable
 - ❑ Power to remain anonymous includes responsibility to use that power wisely